


TELENCO® MINI @ DROP CLAMP FOR ROUND OPTICAL CABLES



LEGEND	
1	Body
2	Bail
3	Mandrel



Telenco® Mini @ drop clamp is used for the dead-ending of 3 to 4mm aerial round drop cables where spans should not exceed 70m. It has been especially designed to receive round optical drop cables with no FRP rods in their outer sheath construction.

This compact clamp presents a mandrel shaped body enabling the roll up and self-tightening of the cable. It includes an opening bail for direct installation on pole fittings, as well as an integrated cable tie.

Telenco® Mini @ drop clamp is made of UV resistant thermoplastic. The Mini @ drop clamp can be secured onto many different types of open or closed hardware (min Ø 10mm).

PN	MODEL	Ø CABLE	MATERIAL	MTL*	PACKG
09942	MINI @	3-4mm	UV resistant thermoplastic	1200N	100 units

* Maximum Tension Load: for the reference cable

PERFORMANCES

This clamp is fully compliant with the following standards and specifications:

- NF EN C-20-540 Climatic ageing test
- ORANGE CCF/DI/BUBL Technical specifications tensile test (2010/05)
- ORANGE CCF/BI/BUBL (20 May 2010) & NF EN 50289-3-13 (August 2003) Technical specification with insertion loss < 0.2 dB Vibration test

INSTALLATION

- On end poles
- When the line is at an angle greater than 25°C (instead of a suspension device) in order to preserve the cable throughout time
- If road crossing (mandatory cable stop on each pole on both sides of the road)
- In case of unbalanced adjacent spans (a 40m span followed by a range of 30m span, for example)
- If rugged terrain (downhill line on the mountainside, for instance)
- In alignment, every 5 poles (in addition to suspension clamps on intermediate poles) or on every pole in double anchoring configurations

FEATURES & BENEFITS

- Single piece, cost-efficient design
- Simple, fast and toolless installation
- Effective cable grip with capstan effect
- Installs directly on pole hardware with Ø 10mm min, eye or pigtail type