


Univers	Professional
Type	Products
Category	Lanyards & Energy Absorbers
Subcategory	Fall-Arrest Energy-Absorbing Lanyards




ABSORBICA®-Y 80


ABSORBICA-Y 80 is a double lanyard with a compact energy absorber, designed for progression on a vertical structure or a horizontal lifeline, and for passing intermediate anchors. It works with users who weigh between 60 and 140 kg. It has several connection options on the harness and can be used with different types of connectors.



The energy absorber's very compact design doesn't hinder the user during progression.



In the event of a fall, the progressive tearing of the energy absorber webbing limits the impact force on the user. The lanyards are designed for users who weigh between 60 and 140 kg.



To help maximize safety during operations, Petzl offers a simple and quick clearance calculator, determined using user weight and lanyard length. Available at [Petzl.com](https://www.petzl.com).



The pouch's simple opening system gives the user quick access to the energy absorber to perform regular inspections.

Short Description Double lanyard with integrated energy absorber

Selling Points

- Designed for progression on a vertical structure or horizontal lifeline, and when passing intermediate anchors
- Absorbs energy in the event of a fall:
 - Progressive tearing of the energy absorber webbing limits the impact force on the user
 - Works with users who weigh between 60 and 140 kg
- Designed for use with a maximum length of 100 cm, including connectors
- Minimal bulk: the energy absorber's very compact design doesn't hinder the user during progression
- Durable fabric pouch with a simple opening system protects the energy absorber from abrasion or contaminants while allowing for regular inspection of the absorber
- Two options for installation on the harness, depending on use:
 - Frequent connection/disconnection: with a carabiner held in correct position by the STRING positioning accessory (included with the lanyard)
 - Semi-permanent connection: with a RING OPEN gated ring, whose circular shape allows optimal positioning
- Two options for connectors at end of lanyard: carabiners or large-opening MGO OPEN connectors

Specification

- Certification(s): CE EN 355
- Certifications depend on the connectors that are used. More information in the Instructions for Use.
- Maximum length with connectors: 100 cm
 - Material(s): Polyester, nylon
-

Specifications by reference

Reference(s)	L012AB00
Length without connectors	70 cm
x	100 cm
Weight	240 g
Made in	RO
Guarantee	3 years
Inner Pack Count	1
Quantity Per Box	10
EAN	3342540846418

Related product(s)	MGO OPEN EASHOOK OPEN Am'D OK NEWTON EASYFIT European Version VOLT® European Version VOLT® European Version MICRO SWIVEL RING OPEN SWIVEL OPEN
--------------------	---