


| | |
|-------------|---------------------------------------|
| Univers | Professional |
| Type | Products |
| Category | Lanyards & Energy Absorbers |
| Subcategory | Fall-Arrest Energy-Absorbing Lanyards |




ABSORBICA®-Y MGO European Version


ABSORBICA-Y MGO is a double lanyard with compact energy absorber, designed for progression on a vertical structure or a horizontal lifeline, and for passing intermediate anchors. It works with users who weigh between 60 and 140 kg. It's ready to use, with two large-opening MGO connectors on the end of the lanyard and an OK TRIACT-LOCK connector for harness attachment. It is available in two versions: 80 (rope arms), or 150 FLEX (elasticized arms).



The energy absorber's very compact design doesn't hinder the user during progression.



In the event of a fall, the progressive tearing of the energy absorber webbing limits the impact force on the user. The lanyards are designed for users who weigh between 60 and 140 kg.



To help maximize safety during operations, Petzl offers a simple and quick clearance calculator, determined using user weight and lanyard length. Available at [Petzl.com](https://www.petzl.com).





The pouch's simple opening system gives the user quick access to the energy absorber to perform regular inspections.

| | |
|-------------------|---|
| Short Description | Double lanyard with integrated energy absorber and MGO connectors |
|-------------------|---|

| | |
|----------------|--|
| Selling Points | <ul style="list-style-type: none">• Designed for progression on a vertical structure or horizontal lifeline, and when passing intermediate anchors• Absorbs energy in the event of a fall:<ul style="list-style-type: none">- Progressive tearing of the energy absorber webbing limits the impact force on the user- Works with users who weigh between 60 and 140 kg• Minimal bulk:<ul style="list-style-type: none">- Energy absorber's very compact design doesn't hinder the user during progression- FLEX version with 150 cm of elasticized webbing to avoid hindering progression• Durable fabric pouch with a simple opening system protects the energy absorber from abrasion or contaminants while allowing for regular inspection of the absorber• Ready-to-use solution: comes with two large-opening MGO connectors on the end of the lanyard and an OK TRIACT-LOCK connector for harness attachment• It is available in two versions: 80 (rope arms), or 150 FLEX (elasticized arms) |
|----------------|--|

| | |
|---------------|--|
| Specification | <ul style="list-style-type: none">• Certification(s): CE EN 355 (the 150 FLEX version meets the requirements of the RFU PPE-R/11.074)• Total length (lanyard + connectors):<ul style="list-style-type: none">- 100 cm for the 80 version- 183 cm for the 150 FLEX version• Material(s): Polyester, nylon, high-modulus polyethylene, aluminum |
|---------------|--|

Specifications by reference

| Reference(s) | L012CB00 | L014CB01 |
|------------------------|---|---|
| |  |  |
| Version | 80 | 150 FLEX |
| Length with connectors | 100 cm | 183 cm |
| Weight | 1260 g | 1250 g |
| Made in | RO | RO |
| Guarantee | 3 years | 3 years |
| Inner Pack Count | 1 | 1 |
| Quantity Per Box | 5 | 5 |
| EAN | 3342540846432 | 3342540846142 |

Related product(s) NEWTON EASYFIT European Version
 VOLT® European Version