

JETSTREAM CABLE BLOWING UNIT



The JetStream has been designed to provide maximum cable protection, combined with the performance and reliability of the hydraulic drive. The profiled double drive belt system is driven by a single 32cc hydraulic motor, powered by the proven Hydraulic power pack. The electronic monitoring system provides a read-out of speed and distance, gives protection against duct obstructions and includes an emergency stop facility. The JetStream is adjustable to suit a wide range of cable diameters 4-20mm, and duct diameters 12-50mm o/d.

FEATURES & BENEFITS

| |
|--|
| Automatic Cable Centralisation |
| Synchronous high grip profiled drive belts |
| Tabletop design |
| Variable speed control |
| Single person operation |
| Digital cable speed and length monitoring |
| Integral air valve and pressure gauge |
| Easy cable threading |
| Polycarbonate safety guarding |
| Low maintenance |
| Wheeled travel case |
| Tool kit |

SHIPPING SPECIFICATION

| | |
|--------|-------|
| Length | 700mm |
| Width | 590mm |
| Height | 550mm |
| Weight | 60Kg |

SPECIFICATION

| | |
|-------------------------|------------------|
| Cable Range | 4-20mm |
| Duct Range | 12-50mm |
| Cable Speed | 85m/min |
| Pushing Force | 600N |
| Maximum Air Pressure | 15 Bar |
| Drive Media | Hydraulic |
| Drive Type | Profiled Belt |
| Drive Orientation | Horizontal |
| Cable Speed Measurement | Proximity Switch |