


## LISA Fiber Cassette

### Description

LISA Fiber Cassette, 12 x LCD adaptor blue, OS2, UPC, TIA  
LC-L-SH-88-12-24-09-H1-04O-S0

### Features

- Cassette accessed from the front with side-facing adaptors with pull-out and hinge-down function for maintenance
- Pull-out service position for immediate access to adaptors
- Patch cords supported and guided into management system
- Various connector types supported - up to 18 x BFF / 36 x SFF
- Design includes bend radius limitation, storage for 1.5m fiber with separation of incoming and pigtail fibers
- Quick installation and easy handling without tools
- Easy to understand labeling and highly visible colour coding of cassette
- Supplied with central splice bridge for heat shrink and sandwich splice protectors for up to 36 fibers



### Technical data

#### Mechanical data

Characteristics	Values
Product family	LISA
Suitable for	Splicing
Dimension (Width x Length x Height) (mm)	262.5 x 293 x 18.5
Dimension (Width x Length x Height) (inch)	10.3 x 11.5 x 0.7
Weight (g)	610
Weight (oz)	21.5
Material module	ABS/PC
Colour module	window grey (RAL 7040)
Number of Adaptor front (pcs)	12
Adaptor type front	LC
Adaptor type front polishing	UPC
Adaptor colour front	blue
Colour code	TIA

#### Optical data


Characteristics	Values
Fiber count	24
Fiber type	Singlemode 9/125 µm OS2
Module insertion loss	Singlemode OS2: <=0.50 dB
Module return loss	Singlemode OS2 PC: >=50dB

#### Environmental data

Characteristics	Values
Temperature resistance (min to max) (°C)	-40 to 70
Temperature resistance (min to max) (°F)	-40 to 158
UL Rating	UL 94 V-0
Free of halogen	Yes
RoHS compliant	Yes
REACH compliant	Yes

## LISA Fiber Cassette

### Technical drawing



### Ordering information

Description	Item number
-------------	-------------

### Related Documents

Installation manual	DOC-0000783226
---------------------	----------------