

# HURRICANE CABLE BLOWING UNIT

**CBS**  
PRODUCTS



The Hurricane has been designed to maximise protection for micro cables with a compliant double drive concept, backed by the latest technology in servo controls to provide precise control of torque and speed. Single person operation with safe, easy to operate ergonomic controls combines with low maintenance and high reliability to form the machine's key features. The Hurricane is adjustable to suit a wide range of cable diameters from 2.5mm to 16mm.

## FEATURES & BENEFITS

Automatic cable centralising
Synchronous high grip profiled compliant drive belts
Vertical design with ergonomic controls for ease of operation
Forward and reverse
Variable torque and speed controls via remote
Digital servo monitor drive system
Auto stop facility when air stone fitted
Single person operation
Digital cable speed and length monitoring
Integral air valve and pressure gauge
Easy cable threading
Polycarbonate safety guiding
Lightweight and compact
Low maintenance
Low noise levels
Travel case
Tool Kit
Advanced data logging measuring speed, force, distance, GPS location and environmental conditions

# HURRICANE CABLE BLOWING UNIT

## SPECIFICATION

Order Code	W2252-UK
Cable Diameter	2.5 to 16 mm
Tube Size (Outside Diameter)	5 to 25 mm
Cable Speed (Adjustable)	0-85 m/min
Pushing Force	400 N
Air Pressure	15 Bar Max
Power Requirement	220 / 110 V AC
Dimensions (L x W x H)	550 x 310 x 350 mm
Weight	24 kg

## HURRICANE UK KIT

Parts included in the Kit	
W2252	Hurricane Cable Blowing Machine
W2252-PS-110	Power Supply Unit 110V
W2252-GN-110	Generator 2 kVA 110V Petrol Inverter Suitcase
W2252-TBC-10	Tube Collet Assembly - 10 mm OD
W2252-TBC-12	Tube Collet Assembly - 12 mm OD
W2252-TBC-14	Tube Collet Assembly - 14 mm OD
W2252-TBC-16	Tube Collet Assembly - 16 mm OD
W2252-TBC-18	Tube Collet Assembly - 18 mm OD
W2252-TBC-20	Tube Collet Assembly - 20 mm OD
W2252-TBC-25	Tube Collet Assembly - 25 mm OD
W2252-TCC-4-6	Cable Guide, 4 - 6 mm Diameter
W2252-TCC-6-9	Cable Guide, 6 - 9 mm Diameter
W2252-TCC-9-12	Cable Guide, 9 - 12 mm Diameter
W2252-TCC-12-14	Cable Guide, 12 - 14 mm Diameter
W2252-TCC-14-16	Cable Guide, 14 - 16 mm Diameter
W2252-CS-4-5	Cable Seals 4 - 5 mm
W2252-CS-5-6	Cable Seals 5 - 6 mm
W2252-CS-6-7.5	Cable Seals 6 - 7.5 mm
W2252-CS-7.5-9	Cable Seals 7.5 - 9 mm
W2252-CS-9-10.5	Cable Seals 9 - 10.5 mm
W2252-CS-10.5-12	Cable Seals 10.5 - 12 mm
W2252-CS-12-14	Cable Seals 12 - 14 mm
W2252-CS-14-16	Cable Seals 14 - 16 mm