

Microduct Connector End Stop



Direct bury straight connector

Robust construction includes IP68 water ingress protection and resistance to high-pressure forces, allowing them to be used in direct buried (DB) applications. The transparent body enables easy visual inspection of the cable within the connector.

FEATURES & BENEFITS

For standard and DB buried application
Compact size
Full plastic design (metal free)
Push fit
No tools needed
Transparent body allows verification of the position of microduct and fibre
Maximum installation: 30 bar
Working temperature: 20°C/+50°C
Fluid: compressed air with blowing system
Microduct to connect: polyethene system
According to standards: CEI EN 50411-2-8
Protection class: IP68

APPLICATION

For standard and DB buried application

DIMENSIONS

Mod.	A	F	L	Weight (g)	Package (pieces)
CV4750 3	3	10	16.5	1.5	100
CV4750 4	4	10	16.5	1.5	100
CV4750 5	5	12.5	21.5	2.5	100
CV4750 7	7	16.5	22.5	3.5	100
CV4750 8	8	17.5	23.5	3.5	100
CV4750 8.5	8.5	17.5	23.5	3.5	100
CV4750 10	10	20.5	26	5	100
CV4750 12	12	23	28	7	100
CV4750 12.7	12,7	23	28	7	100
CV4750 14	14	25.5	32.5	9	100
CV4750 16	16	30	36	13.5	50
CV4750 18	18	33.5	42	19	50
CV4750 20	20	37.5	45.5	25	50