

MINI-CSP 4FO

MINI CUSTOMER SPLICE POINT 4FO



To deliver the best FTTP experience, the Mini CSP is engineered for discretion, ease of use, and fast deployment. Its ultra-compact, low-profile design fits standard UK faceplates, blending seamlessly into residential or commercial exteriors. Ideal for both new-builds and retrofits, it reduces visual impact while maintaining full functionality. By streamlining installation and minimizing the need for materials or rework, it helps reduce both deployment costs and environmental footprint.

FEATURES & BENEFITS

- Compact and rugged design
- Easy installation and maintenance
- Safe and secure cable management
- Reliable communication
- Time and cost-effective installation
- UK standard compliance and capping compatibility
- Flexible cable storage

TECHNICAL SPECIFICATIONS

- Enclosure Type: Outdoor
- Box dimensions: L98.5mm x H 112mm x D 21mm
- Box material: ABS Grey
- IP rating: IP55
- Cable entry points: 2 Input/2 Output
- Bend radius min: 30mm
- Connector type: Splice only
- Splicing count: 4 – 40 x 2.2mm
- Input cable diameter max: 3-8mm Round Cable or Flat Cable up to 8.5mm
- Output cable diameter max: 3-8mm Round Cable or Flat Cable up to 8.5mm



ADDITIONAL ACCESSORIES



BT Capping 25

BT Connector Bend No.4

BT Cover 101A

PN	MODEL	DIMENSIONS	WEIGHT	PACKG	PACKAGING DIMENSIONS	QUANTITY PER PALLET
1010166	MINI-CSP 4FO	98.5 x 112 x 21mm	0.24kg	144	480 x 400 x 300mm	5184