


OTO HESTIA SP 1-4 FO

OPTICAL TERMINATION OUTLET 1-4 FO WALL MOUNTING



1 / 2 / 4FO



The OTO HESTIA SP 1 to 4FO is an optical fiber network terminal outlet installed at the customer accommodation. This OTO allows a wall fixation with a reduce depth impact.

Available in 1, 2 and 4FO; with adapter, adapter and pigtail, pre-connectorised, the OTO is perfectly suited for all indoor installation configurations.



Dimensions: L 80 x H 80 x D 24mm



Weight: 0.1kg

FEATURES & BENEFITS

- Wall mounting or on flush-box mounting (OTO very flat: Depth 24mm).
- Removable cover without tools.
- Connection cable insertable from the rear, sides, bottom or top of the socket.
- Fiber guidance ensuring a bending radius of 15mm.
- Transparent front flap to protect the subscriber identification label.
- Reversible tray to meet field constraints (corner installation).
- Laser and dust protection flap(s) for the optical ports integrated into the OTO.



Reversible tray



TECHNICAL SPECIFICATION

- Cable entry: up to Ø 4.5mm for all entries / up to 5.2mm for the bottom entry
- Number of cable entries: 5
- Maximum capacity: 1/2/4 SC connectors and 1/2/4 splices
- Operating temperature: -10°C to 60°C
- Material / Color: ABS-PC / White RAL 9010
- Bending radius: $\geq 15\text{mm}$
- Optical performances (IEC-61300-3-4):
IL $\leq 0.3\text{dB}$, RL $\geq 60\text{dB}$
- UV protection
- UL94V0

REFERENCES

REF.	DESIGNATION	PACKAGING	QUANTITY PER PALLET
1001815	OTO HESTIA SP 1FO with adaptor and pigtail SC/APC*	20	1600
1001962	OTO HESTIA SP 2 FO with adaptors and pigtails SC/APC*	20	1600
1001816	OTO HESTIA SP 4FO with adaptors and pigtails SC/APC*	20	1600

* - Delivered with screws 3,5 x 30mm and plugs

- Adaptors and pigtails delivered non assembled

- For DIN rail fixation, use standard OTO HESTIA delivered with an additional plate - refer to the Datasheet OTO HESTIA.