DATASHEET

GATEGUARD 4-SIDED UTILITY BARRIER

STREET WORKS BARRIERS

Telenco









Non-contractual photo

The Gateguard Plastic 4-Sided Utility Barrier provides a highly visible temporary barrier for manholes, utility works and street works. Its four-sided modular design creates a clearly defined working area while remaining lightweight and easy to handle on site.

Each hinged gate weighs just 2kg and measures 750mm long x 1000mm high, allowing the barrier to be quickly positioned, folded and transported between jobs. Hinged clips and an integral locking clamp support quick assembly and provide additional stability when the barriers are configured in a straight line. Manufactured in the UK from durable high-density polyethylene (HDPE), the barrier is 100% recyclable. Its folding modular construction also makes it particularly useful where vehicle space or site access is restricted.

For enhanced stability, the Gateguard can be used with SafeBase units, each weighing 2.6kg, to achieve Category A wind loading up to 59mph. The barrier meets the reflectivity requirements of BS EN 12899-1 and complies with relevant Chapter 8 street works requirements.

- **Gate Size:** 750mm long x 1000mm high
- **Gate Weight:** 2kg each (four hinged gates)
- **Wind Loading:** Category A, up to 59mph with SafeBase
- **Openreach Ref:** 081521

KEY FEATURES

- Four-sided utility barrier for manholes and street works
- High-visibility design
- Four hinged gates
- Lightweight 2kg individual gate weight
- 750mm gate length
- 1000mm barrier height
- Folds for easy transportation and storage
- Hinged clips for quick assembly
- Integral locking clamp
- Modular design allows different configurations
- Manufactured from durable HDPE
- 100% recyclable
- Manufactured in the UK
- Can be used with SafeBase for enhanced stability
- Category A wind loading up to 59mph when used with SafeBase
- Suitable for restricted-access sites
- BT Openreach reference 081521

TECHNICAL SPECIFICATION

Product type	4-Sided Utility Barrier
Application	Manholes / Utility Works
Material	High-Density Polyethylene (HDPE)
Number of sides	4
Gate length	750mm
Height	1000mm
Individual gate weight	2kg
SafeBase weight	2.6kg each
Wind loading	Category A, up to 59mph when used with SafeBase
Configuration	Hinged / Modular
Storage	Folding
Recyclable	100%
Manufactured in	UK
BT Openreach reference	081521

COMPLIANCE

- BS EN 12899-1 reflectivity requirements
- Chapter 8 Street Works compliant
- Safety at Street Works & Road Works - A Code of Practice
- Traffic Signs Regulations & General Directions

APPLICATIONS

- Manhole protection
- Telecoms street works
- Utility maintenance
- Underground network access
- Fibre network installation
- Openreach infrastructure works
- Temporary work area segregation
- Roadside and footway works
- Restricted-access work sites


ASSOCIATED ITEMS



Gateguard - Red/White 1 Panel Metal Gate Guard
Product code: GATE/1



SafeBase - Avalon Barrier ClearPath
Product code: BARR/A/CPF



Gate Guard Clip
Product code: CLIP/1