

VANTAGE™ OUTDOOR WALL BOX

OUTDOOR CABINETS



Designed to protect active IT and telecom equipment in exposed and space-constrained environments, the Vantage™ Outdoor Wall Box provides a compact, secure and configurable wall-mounted enclosure solution.

Available in multiple heights and depths, with passive, fan-assisted or vented-and-filtered cooling options, Vantage™ enables a tailored enclosure specification for edge network, rail, roadside, utility and remote infrastructure deployments.

FEATURES & BENEFITS

- **Weather-resistant enclosure:** Designed for outdoor use, providing protection against dust, water ingress and environmental exposure.
- **Configurable cooling options:** Available with no active cooling, fan-and-filter cooling, or vented-and-filtered airflow arrangements to suit installed equipment heat loads.
- **Flexible enclosure sizing:** Configurable in 6U, 9U and 12U heights, with 300 mm, 400 mm or 500 mm depth options.
- **Secure equipment protection:** Single front door with black composite lockable swing handle helps prevent unauthorised access to installed equipment.
- **19-inch equipment mounting:** Supplied with 19-inch mounting verticals for straightforward installation of standard rack-mounted telecom and network equipment.
- **Cable-entry provision:** Removable roof & base gland plates enable sealed cable entry while supporting installation flexibility.
- **Wall-mount installation:** Four external mounting brackets provide a secure and practical wall-fixing arrangement.
- **Durable powder-coated finish:** Polyester powder-coated steel construction in Light Grey provides a robust, clean finish suited to infrastructure environments.

TECHNICAL SPECIFICATION

- **Product range:** Vantage™ Outdoor Wall Box
- **Enclosure type:** Wall-mounted outdoor equipment enclosure
- **Available heights:** 6U, 9U, 12U
- **Width:** 600 mm
- **Available depths:** 300 mm, 400 mm, 500 mm
- **Equipment mounting:** 19-inch mounting verticals
- **Door configuration:** Single front door
- **Door handle:** Black composite lockable swing handle
- **Mounting arrangement:** Four external wall-mounting brackets
- **Cable entry:** Removable roof gland plate
- **Cooling options:** None / Fan & Filter / Vented & Filtered
- **Finish:** Polyester powder coated
- **Standard colour:** Light Grey
- **Typical ingress protection:** IP65 — subject to final cooling and cable-entry configuration

