# TECHNICAL SPECIFICATION



# 500 Series Moulded Masks

Disposable Moulded Mask FFP3 Valved (532) Box 5 / BEK130-002-M00



### **DESCRIPTION**

Disposable mask with  $360^{\circ}$  comfort foam and exhalation valve for low breathing resistance. The adjustable 4-point head strap means it can be fitted comfortably to all head sizes and shapes.

## **OPTIONS**

Disposable Moulded Mask FFP3 Valved (532) Box 5 (BEK130-002-M00)

# SAFETY STANDARDS

EN 149















#### **SPECIFICATIONS**

Classification

FFP3 (Filtering Facepiece Particulate)

Usage

NR (Non-Reusable)



Activated Carbon Layer

No

Maximum Total Inward Leakage (TIL)

2%

**UK Assigned Protection Factor** 

20



Exhalation Valve

Yes



Nose Bridge Moulded

Metal Free

Yes

Filter Shelf Life

5 Years



Filter Type

P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging

Yes – D marking = passes optional clogging test

Minimum Filtration Efficiency 99% For FFP3 Rated

Nominal Protection Factor

50

Mask Design Moulded



4 Point Harness adjustment system

Yes

Latex free

Yes

Mask Material Polypropylene



**Product Weight** 

15g

#### **FEATURES**



#### **Exhalation Valve**

Low resistance exhalation valve for easy breathing.



# 4-Point Adjustable Straps

Metal free, 4-point adjustable straps create a firm and adaptable fit.



#### Foam Padded Nose Bridge

A mouldable nose bridge and 360° foam area around the inside provide comfort and a firmer fit.

# RANGE



# DOWNLOADS



doc-disposable-dust-masks-500-series-532.pdf (PDF)

doc-disposable-dust-masks-500-series-532.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





